

according to Regulation (EC) No. 1907/2006

Print Date: 06.03.2013 Revision Date: 04.03.2013 Page **1** of **13**

Commercial Product Name: CUROX M-312

DE / EN Version: 1.3

1. Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product information

Commercial Product Name : CUROX M-312

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Substance/Mixture : Hardener

1.3 Details of the supplier of the safety data sheet

Company : United Initiators GmbH & Co. KG

Dr. Gustav-Adolph-Str. 3

82049 Pullach Germany

E-mail address : contact@united-in.com

1.4 Emergency telephone number

+49 / 89 / 74422 - 0

In case of an emergency in the United States, contact:

For chemical Emergency ONLY call CHEMTREC : 1-800-424-9300

For ALL other inquiries about this product call

United Initiators Inc.

555 Garden Street, Elyria Ohio 44035 at 1 (440) 323-3112

2. Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Flammable liquids, Category 3

Organic peroxides, Type D

Acute toxicity, Category 4

H226: Flammable liquid and vapour.

H242: Heating may cause a fire.

H302: Harmful if swallowed.

Skin corrosion, Category 1B H314: Causes severe skin burns and eye damage.

Classification (67/548/EEC, 1999/45/EC)

Oxidising R 7: May cause fire.

R10: Flammable.

Corrosive R34: Causes burns.

Harmful R22: Harmful if swallowed.

2.2 Label elements



according to Regulation (EC) No. 1907/2006

Commercial Product Name: CUROX M-312

DE / EN Version: 1.3

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :







Signal word : Danger

Hazard statements : H226 Flammable liquid and vapour.

H242 Heating may cause a fire. H302 Harmful if swallowed.

H314 Causes severe skin burns and eye damage.

Precautionary statements : **Prevention:**

P210 Keep away from heat/sparks/open flames/hot

surfaces. - No smoking.

P220 Keep/Store away from clothing/ strong acids,

bases, heavy metal salts and other reducing

substances /combustible materials.

P235 Keep cool.

P262 Do not get in eyes, on skin, or on clothing.
P280 Wear protective gloves/ protective clothing/ eye

protection/ face protection.

Response:

P303 + P361 + P353 IF ON SKIN (or hair): Remove/ Take off immedi-

ately all contaminated clothing. Rinse skin with

water/ shower.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for

several minutes. Remove contact lenses, if pre-

sent and easy to do. Continue rinsing.

P315 Get immediate medical advice/ attention.
P378 Use dry sand, dry chemical or alcohol-resistant

foam for extinction.

Storage:

P403 + P233 Store in a well-ventilated place. Keep container

tightly closed.

Disposal:

P501 Dispose of contents/ container to an approved

waste disposal plant.

Hazardous components which must be listed on the label:

• 1338-23-4 methylethylketoneperoxide

Labelling according to EC Directives: 1999/45/EC

Hazard symbols





Oxidising Corrosive



according to Regulation (EC) No. 1907/2006

Print Date: 06.03.2013 Revision Date: 04.03.2013 Page **3** of **13**

Commercial Product Name: CUROX M-312

DE / EN Version: 1.3

R-phrase(s) : R7 May cause fire. Flammable. R10 Harmful if swallowed. R22 R34 Causes burns. S-phrase(s) : S 3/7 Keep container tightly closed in a cool place. Keep away from strong acids, bases, heavy S14 metal salts and other reducing substances. S26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. S36/37/39 Wear suitable protective clothing, gloves and eye/face protection. S45 In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible). S50 Do not mix with activators and catalyst promot-

Hazardous components which must be listed on the label:

• 1338-23-4 methylethylketoneperoxide

2.3 Other hazards

This mixture contains no substance considered to be persistent, bioaccumulating nor toxic (PBT).

3. Composition/information on ingredients

3.2 Mixtures

Hazardous components

Chemical Name	CAS-No. EC-No. Registration number	Classification (67/548/EEC)	Classification (1272/2008/EC)	Concentration [%]
methylethylketoneperoxid e	1338-23-4 215-661-2 01- 2119514691- 43-0000	O; R 7 Xn; R22 C; R34	Org. Perox. D; H242 Acute Tox. 4; H302 Skin Corr. 1B; H314	25 - < 35
4-hydroxy-4- methylpentan-2-one	123-42-2 204-626-7	Xi; R36	Eye Irrit. 2; H319	12,5 - < 15
butanone	78-93-3 201-159-0	F; R11 R66 R67 Xi; R36	Flam. Liq. 2; H225 Eye Irrit. 2; H319 STOT SE 3; H336	3 - < 5
hydrogen peroxide solution	7722-84-1 231-765-0	O; R 8 R 5	Ox. Liq. 1; H271 Acute Tox. 4; H332	3 - < 5



according to Regulation (EC) No. 1907/2006

Print Date: 06.03.2013 Revision Date: 04.03.2013 Page 4 of 13

Commercial Product Name: CUROX M-312

DE / EN Version: 1.3

C: R35 Acute Tox. 4: H302 Xn; R20/22 Skin Corr. 1A; H314

For the full text of the R-phrases mentioned in this Section, see Section 16. For the full text of the H-Statements mentioned in this Section, see Section 16.

4. First aid measures

4.1 Description of first aid measures

General advice Take off all contaminated clothing immediately. Never give anything

> by mouth to an unconscious person. Remove from exposure, lie down. In the case of accident or if you feel unwell, seek medical

advice immediately (show the label where possible).

If inhaled : Remove to fresh air. Call a physician immediately.

In case of skin contact : Wash off immediately with soap and plenty of water.

In case of eye contact : In the case of contact with eyes, rinse immediately with plenty of

water and seek medical advice.

If swallowed : Clean mouth with water and drink afterwards plenty of water. If a

person vomits when lying on his back, place him in the recovery position. Do NOT induce vomiting. If swallowed, seek medical advice

immediately and show this container or label.

4.2 Most important symptoms and effects, both acute and delayed

no data available

4.3 Indication of any immediate medical attention and special treatment needed

no data available

5. Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media Use water spray, alcohol-resistant foam, dry chemical or carbon

dioxide.

Unsuitable extinguishing media : High volume water jet

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-

fighting

: Cool closed containers exposed to fire with water spray. Do not allow

run-off from fire fighting to enter drains or water courses.

5.3 Advice for firefighters

firefighters

Special protective equipment for : Use personal protective equipment.



according to Regulation (EC) No. 1907/2006

Commercial Product Name: CUROX M-312

DE / EN Version: 1.3

Further information : Fire residues and contaminated fire extinguishing water must be

disposed of in accordance with local regulations.

6. Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Wear respiratory protection. Wear personal protective equipment.

6.2 Environmental precautions

Avoid subsoil penetration. Do not allow material to contaminate ground water system. Do not contaminate water. If the product contaminates rivers and lakes or drains inform respective authorities. Do not let product enter drains.

6.3 Methods and materials for containment and cleaning up

Remove mechanically and with care (e.g. with clean polyethylene plastic shovel). Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).

6.4 Reference to other sections

see chapter: 7, 8, 11, 12 and 13

6.5 Other information

Never add other substances or waste material to product residue. Offer surplus and non-recyclable solutions to a licensed disposal company.

7. Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : For personal protection see section 8.

Dust explosion class : no data available

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas

and containers

Electrical installations / working materials must comply with the technological safety standards. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Keep con-

tainer tightly closed. No smoking.

Further information on storage

conditions

: Avoid impurities (e.g. rust, dust, ash), risk of decomposition.

Advice on common storage : Store apart from other dangerous and incompatible substances.

Storage temperature : < 30 °C

Other data : Storing temperature for reasons of quality



according to Regulation (EC) No. 1907/2006

Print Date: 06.03.2013 Revision Date: 04.03.2013 Page 6 of 13

Commercial Product Name: CUROX M-312

DE / EN Version: 1.3

liquid up to -25 °C

7.3 Specific end use(s)

no data available

8. Exposure controls/personal protection

8.1 Control parameters

Components	CAS-No.	Control parameters	Basis	Update
4-hydroxy-4-methylpentan-2-one	123-42-2	AGW: 96 mg/m3, 20 ppm DFG, H,	DE TRGS 900	2006-01-01
butanone	78-93-3	AGW: 600 mg/m3, 200 ppm DFG, EU, H, Y,	DE TRGS 900	2010-08-04
Components	CAS-No.	Control parameters	Basis	Update
butanone	78-93-3	TWA: 600 mg/m3, 200 ppm	2000/39/EC	2000-06-16
		STEL: 900 mg/m3, 300 ppm		

Other information on limit values: see chapter 16

Biological occupational exposure limits - TRGS903

Substance name	CAS-No.	Control parameters	Sampling time	Update
butanone	78-93-3	2-butanon: 5 mg/l ()	b	2011-12-19

Remarks:

No time limit а

Immediately after exposition or after working hours b c d In case of long-term exposition: after more than one shift

Before the next shift

8.2 Exposure controls

Engineering measures

Provide adequate ventilation.

Personal protective equipment

Respiratory protection : Short duration filter unit: Filter A



according to Regulation (EC) No. 1907/2006

Print Date: 06.03.2013 Revision Date: 04.03.2013 Page **7** of **13**

Commercial Product Name: CUROX M-312

DE / EN Version: 1.3

Hand protection

Material : butyl-rubber
Glove thickness : 0,5 mm
Breakthrough time: : >= 8 h

Remarks : Skin should be washed after contact.

Eve protection : Tightly fitting safety goggles

Wear face protection.

Skin and body protection : Protective suit

Remove and wash contaminated clothing before re-use.

<u>Hygiene measures</u>: Wash hands before breaks and immediately after handling the prod-

uct.

Keep away from food, drink and animal feedingstuffs.

Environmental exposure controls

General advice : Avoid subsoil penetration.

Do not allow material to contaminate ground water system.

Do not contaminate water.

If the product contaminates rivers and lakes or drains inform respec-

tive authorities.

Do not let product enter drains.

9. Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance : liquid

Colour : colourless

Odour : characteristic

Odour Threshold : Not relevant

pH : not applicable

Melting point/freezing point : < -25 °C

Initial boiling point and boiling

: not applicable, Decomposition

range

Flash point : 57 °C

Method: ISO 3679

Evaporation rate : Not relevant Flammability (solid, gas) : not applicable

Lower explosion limit : not applicable



according to Regulation (EC) No. 1907/2006

Print Date: 06.03.2013 Revision Date: 04.03.2013 Page **8** of **13**

Commercial Product Name: CUROX M-312

DE / EN Version: 1.3

Upper explosion limit : not applicable Vapour pressure : 0,184 Pa at 25 °C

Relative vapor density : no data available
Density : 1,01 g/cm3 at 20 °C

Water solubility : ca. 6,5 g/l at 20 °C

Partition coefficient: n- : log Pow: < 0,3 at 25 °C

octanol/water

Solubility in other solvents : Mixable

Medium: Phthalates

Auto-ignition temperature : not applicable, Decomposes on heating.

Decomposition temperature : ca. 60 °C, SADT (UN test H.4), SADT possible at tempera-

tures above approximately 60 °C.

Viscosity, dynamic : 13 mPa.s at 20 °C

Viscosity, kinematic : no data available Explosive properties : no data available Oxidizing properties : Organic peroxide

9.2 Other information

Refractive index : 1,431

at 20 °C

10. Stability and reactivity

10.1 Reactivity

Stable under recommended storage conditions.

10.2 Chemical stability

Contact with incompatible substances can cause disintegration at or below SADT.

10.3 Possibility of hazardous reactions

Vapours may form explosive mixture with air.

Stability : Stable under recommended storage conditions.

10.4 Conditions to avoid

Keep away from heat and sources of ignition.

10.5 Incompatible materials

Materials to avoid : Accelerators, strong acids and bases, heavy metals and heavy metal

salts, reducing agents, Avoid impurities (e.g. rust, dust, ash), risk of

decomposition.



according to Regulation (EC) No. 1907/2006

Print Date: 06.03.2013 Revision Date: 04.03.2013 Page **9** of **13**

Commercial Product Name: CUROX M-312

DE / EN Version: 1.3

10.6 Hazardous decomposition products

Hazardous decomposition prod-

ucts

Irritant, caustic, flammable, noxious/toxic gases and vapours can

develop in the case of fire and decomposition

11. Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Acute oral toxicity : LD50 rat: 1.017 mg/kg

Test substance: methylethylketoneperoxide (40% in

dimethylphthalate)

Acute inhalation toxicity : LC50 rat: 17 mg/l

Exposure time: 4 h

Test substance: methylethylketoneperoxide (40% in

dimethylphthalate)
Note: Aerosol
Nominal concentration

Acute dermal toxicity : LD50 rat: 4.000 mg/kg

Test substance: methylethylketoneperoxide (40% in

dimethylphthalate)

Skin corrosion/irritation

<u>Skin irritation</u> : Causes burns.

Serious eye damage/eye irritation

<u>Eye irritation</u> : Causes burns.

Respiratory or skin sensitization

Sensitisation : Method: Maximisation Test

Test substance: methylethylketoneperoxide (60% in

dimethylphthalate/diacetone alcohol)

Did not cause sensitization on laboratory animals.

Germ cell mutagenicity

Genotoxicity in vitro : Result: Not mutagenic in Ames Test.

Carcinogenicity
no data available

Reproductive toxicity

no data available



according to Regulation (EC) No. 1907/2006

Print Date: 06.03.2013 Revision Date: 04.03.2013 Page 10 of 13

Commercial Product Name: CUROX M-312

DE / EN Version: 1.3

Teratogenicity

no data available

STOT - single exposure

butanone : May cause drowsiness or dizziness.

hydrogen peroxide solution : May cause respiratory irritation.

STOT - repeated exposure

no data available

Aspiration hazard

Aspiration toxicity

no data available

12. Ecological information

12.1 Toxicity

<u>Toxicity to fish</u> : LC50 (Poecilia reticulata (guppy)): 44,2 mg/l

Exposure time: 96 h

Test substance: methylethylketoneperoxide (33% in

dimethylphthalate)

Toxicity to daphnia and other

aquatic invertebrates

: EC50 (Daphnia): 39 mg/l

Exposure time: 48 h

Test substance: methylethylketoneperoxide (40% in

dimethylphthalate)

<u>Toxicity to algae</u> : EC50 (Pseudokirchneriella subcapitata): 5,6 mg/l

Exposure time: 72 h

Test substance: methylethylketoneperoxide (40% in

dimethylphthalate)

Toxicity to bacteria : EC50 (Bacteria): 48 mg/l

Exposure time: 30 min

Test substance: methylethylketoneperoxide (33% in

dimethylphthalate)

12.2 Persistence and degradability

<u>Biodegradability</u> : Result: Readily biodegradable.

Method: Closed Bottle test

Test substance: methylethylketoneperoxide (MEKP)

12.3 Bioaccumulative potential



according to Regulation (EC) No. 1907/2006

Commercial Product Name: CUROX M-312

DE / EN Version: 1.3

no data available

12.4 Mobility in soil

no data available

12.5 Results of PBT and vPvB assessment

This mixture contains no substance considered to be persistent, bioaccumulating nor toxic (PBT).

12.6 Other adverse effects

no data available

13. Disposal considerations

13.1 Waste treatment methods

Advice on disposal and packag-

ıng

Disposal:

Dispose of in conjunction with appropriate waste disposal authorities

and in accordance with disposal regulations.

Waste codes should be assigned by the user based on the applica-

tion for which the product was used.

14. Transport information

ADR

UN number : 3105

Description of the goods : ORGANIC PEROXIDE TYPE D, LIQUID

(methylethylketoneperoxide)

Class : 5.2
Packing group : -Classification Code : P1
Labels : 5.2
Limited quantity : LQ16
Tunnel restriction code : (D)
Environmentally hazardous : no

RID

UN number : 3105

Description of the goods : ORGANIC PEROXIDE TYPE D, LIQUID

(methylethylketoneperoxide)

Class : 5.2
Packing group : -Classification Code : P1
Labels : 5.2
Limited quantity : LQ16
Environmentally hazardous : no

IATA



according to Regulation (EC) No. 1907/2006

Print Date: 06.03.2013 Revision Date: 04.03.2013 Page 12 of 13

Commercial Product Name: CUROX M-312

DE / EN Version: 1.3

UN number

Description of the goods Organic peroxide type D, liquid

(methylethylketoneperoxide)

Class 5.2

Packing group

Labels 5.2 (HEAT) 570

Packing instruction (cargo air-

Environmentally hazardous no Packing instruction (passenger 570

aircraft)

IMDG

UN number

Description of the goods ORGANIC PEROXIDE TYPE D, LIQUID

no

(methylethylketoneperoxide)

Class 5.2 Packing group 5.2 Labels EmSNumber 1 F-J EmS Number 2 S-R

Special precautions for user

see chapter: 6, 7 and 8

Marine Pollutant

15. Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

National legislation

Water contaminating class : WGK 2 (water endangering)

(Germany) Classification according VwVwS, Annex 4.

Other regulations : BGV B4 organische Peroxide. (German regulatory requirements)

BG-Merkblatt M001 beachten (German regulatory requirements) Produkt unterliegt nicht dem Sprengstoffgesetz (SprengG). (German regulatory requirements) Take note of Dir 92/85/EEC on the safety and health at work of pregnant workers. Take note of Dir 94/33/EC on the protection of young people at work. Störfallverordnung

Anhang I (German regulatory requirements)

Gefahrengruppe nach § 3 BGV B4: (German regulatory require-

ments) II (German regulatory requirements)

15.2 Chemical Safety Assessment

no data available



according to Regulation (EC) No. 1907/2006

Commercial Product Name: CUROX M-312

DE / EN Version: 1.3

16. Other information

Full text of R-phrases referred to under sections 2 and 3

R 5 Heating may cause an explosion.

R 7 May cause fire.

R 8 Contact with combustible material may cause fire.

R10 Flammable. R11 Highly flammable.

R20/22 Harmful by inhalation and if swallowed.

R22 Harmful if swallowed.
R34 Causes burns.
R35 Causes severe burns.
R36 Irritating to eyes.

R66 Repeated exposure may cause skin dryness or cracking.

R67 Vapours may cause drowsiness and dizziness.

Full text of H-Statements referred to under sections 2 and 3.

H225 Highly flammable liquid and vapour.
H226 Flammable liquid and vapour.
H242 Heating may cause a fire.

H271 May cause fire or explosion; strong oxidiser.

H302 Harmful if swallowed.

H314 Causes severe skin burns and eye damage.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H336 May cause drowsiness or dizziness.

Other information

DFG Senate commission for the review of compounds at the work place dangerous for the

health (MAK-commission).

EU European Union (The EU has established a limit value: deviations in value and peak limit

are possible)

H Skin absorption

Y When there is compliance with the OEL and biological tolerance values, there is no risk of

harming the unborn child

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.